



BA14

LED Bar

Recessed



HOUSING

Electrostatic powder paint coated extruded aluminum housing
IP40 Protection
Electrical Safety Class III

Body Color Options



OPTIC

PC Diffuser
IEC/EN 62471 Photo-Biologic Protection RGO
UGR (CIE Pub.117):21

Optic Options



LED

SMD LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



Ra>80

CCT



CONTROL

Rated Input Voltage 220~240VAC
Range of Input Voltage 198~264VAC
Frequency 50~60Hz
Power Factor PF>0.95
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver

Additional Features



Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)




STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-2
Driver Standarts -

BA14

LED Bar

Recessed

 <p>BA14-AD10 60 LED/m</p>		Power	Lum. Flux	Efficiency	Packaging Sizes			
		14W	873 lm	61 lm/W	Width	- cm	Length	- cm
 <p>BA14-BD10 120 LED/m</p>		Power	Lum. Flux	Efficiency	Packaging Sizes			
		14W	1002 lm	69 lm/W	Width	- cm	Length	- cm
 <p>BA14-CD10 168 LED/m</p>		Power	Lum. Flux	Efficiency	Packaging Sizes			
		14W	1164 lm	78 lm/W	Width	- cm	Length	- cm
					Height	- cm	Amount per ctn.	- pcs.
					Ctn. weight	- kg	Deci	-

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

BA14		BD10		014	-	8	65	S	-9006-PCD8-	2	X	X	S	20
GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACSESSORY	IP		
BA14	AD10 BD10 CD10	014: 14W	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K MB: Amber RD: Red GR: Green BL: Blue	S: Standart	9006: Gri	PCD8: PC %80	2: 24V			S: Standart K: İki Uç Kablolu W: IP65 Soketli	20: IP20		