



Recessed Aluminum LED Bar 24V

Housing

Eloxal coated extruded aluminum.

Diffuser

Polycarbonate Opal diffuser.

PCB

Aluminum PCB.

LED

SMD LED with high color rendering index minimum lifetime of 100.000 hours (L70-85°C)..

Option

- Special Dimensions of 100mm and above.
- Current protection.

Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Voltage	Weight	Measurements
Recessed LED Bar	312275	2700K		3-36W	24V	0,25 Kg	1000mm
Recessed LED Bar	312375	3000K					
Recessed LED Bar	312475	4000K					
Recessed LED Bar	312675	6500K					
Recessed LED Bar	312175	Amber					
Recessed LED Bar	312775	Red					
Recessed LED Bar	312875	Green					
Recessed LED Bar	312975	Blue					
Recessed LED Bar	312276	2700K		3-36W	24V	0,25 Kg	1000mm
Recessed LED Bar	312376	3000K					
Recessed LED Bar	312476	4000K					
Recessed LED Bar	312676	6500K					
Recessed LED Bar	312176	Amber					
Recessed LED Bar	312776	Red					
Recessed LED Bar	312876	Green					
Recessed LED Bar	312976	Blue					
Recessed LED Bar	312277	2700K		3-36W	24V	0,25 Kg	1000mm
Recessed LED Bar	312377	3000K					
Recessed LED Bar	312477	4000K					
Recessed LED Bar	312677	6500K					
Recessed LED Bar	312177	Amber					
Recessed LED Bar	312777	Red					
Recessed LED Bar	312877	Green					
Recessed LED Bar	312977	Blue					

(1) The specified luminous flux values may vary by %10.

(2) 32XY42 X= 0 White Y= 3 3000K
 2 Grey 4 4000K
 3 Black 6 6500K