



## Surface Mounted COB LED Downlight Lighting

### Housing

Electrostatic powder paint coated die cast aluminum Housing.

### Reflector

High purity anodized aluminum reflector.

### LED

≥100.000 hours COB LED with color rendering index.


### Driver

Constant current output, high efficiency driver.


### Option

- ▶ Emergency Lighting kit for 1 or 3 hours period.
- ▶ DIM/DALI DIM

### Housing Color



### Light Angle



### Light Color



Product Name	Order Code <sup>(2)</sup>	CCT (K)	Luminous Flux <sup>(1)</sup>	Power	Voltage	Weight	Measurements
COB Downlight	740350	3000K	1800 lm	15W	220VAC	1,50 Kg	Ø118mm 145mm
COB Downlight	740450	4000K	1929 lm				
COB Downlight	740650	6500K	2079 lm				
COB Downlight	740351	3000K	2800 lm	20W	220VAC	1,50 Kg	Ø118mm 145mm
COB Downlight	740451	4000K	2909 lm				
COB Downlight	740651	6500K	3000 lm				
COB Downlight	740348	3000K	1800 lm	20W	220VAC	1,50 Kg	Ø118mm 188mm
COB Downlight	740448	4000K	1929 lm				
COB Downlight	740648	6500K	2079 lm				
COB Downlight	740349	3000K	2800 lm	30W	220VAC	1,50 Kg	Ø118mm 188mm
COB Downlight	740449	4000K	2909 lm				
COB Downlight	740649	6500K	3000 lm				

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X=0 White Y=3 3000K  
2 Grey 4 4000K  
3 Black 6 6500K



## Surface Mounted COB LED Downlight Lighting

### Housing

Electrostatic powder paint coated die cast aluminum Housing.

### Reflector

High purity anodized aluminum reflector.

### LED

≥100.000 hours COB LED with color rendering index.

### Driver

Constant current output, high efficiency driver.


### Option

- ▶ Emergency Lighting kit for 1 or 3 hours period.
- ▶ DIM/DALI DIM

### Housing Color



### Light Angle



### Light Color



Product Name	Order Code <sup>(2)</sup>	CCT (K)	Luminous Flux <sup>(1)</sup>	Power	Voltage	Weight	Measurements
COB Downlight	240342	3000K	1800 lm	20W	220VAC	1,50 Kg	
COB Downlight	240442	4000K	1929 lm				
COB Downlight	240642	6500K	2079 lm				
COB Downlight	240343	3000K	2800 lm	30W	220VAC	1,50 Kg	
COB Downlight	240443	4000K	2909 lm				
COB Downlight	240643	6500K	3000 lm				
COB Downlight	240344	3000K	3175 lm	40W	220VAC	1,50 Kg	
COB Downlight	240444	4000K	3658 lm				
COB Downlight	240644	6500K	3880 lm				

(1) The specified luminous flux values may vary by %10.

(2) 32XY42 X= 0 White Y= 3 3000K  
 2 Grey 4 4000K  
 3 Black 6 6500K