



Recessed COB LED Downlight Lighting

Housing

Electrostatic powder paint coated die cast aluminum housing.

Reflector

High purity anodized aluminum.

LED

≥100.000 hours COB LED with high color rendering index.

Driver

Constant current output, high efficiency driver.

Option

- ▶ Emergency Lighting kit for 1 or 3 hours period.
- ▶ DIM/DALI DIM


Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Montage Dimens.	Voltage	Weight	Measurements
Recessed COB Downlight	350315	3000K	690 lm	8W	Ø75mm	220VAC	1,20 Kg	
Recessed COB Downlight	350415	4000K	850 lm					
Recessed COB Downlight	350615	6500K	1000 lm					
Recessed COB Downlight	350316	3000K	1160 lm	12W	Ø80mm	220VAC	1,20 Kg	
Recessed COB Downlight	350416	4000K	1350 lm					
Recessed COB Downlight	350616	6500K	1700 lm					
Recessed COB Downlight	350317	3000K	1840 lm	18W	Ø100mm	220VAC	1,20 Kg	
Recessed COB Downlight	350417	4000K	1950 lm					
Recessed COB Downlight	350617	6500K	2100 lm					
Recessed COB Downlight	350318	3000K	2300 lm	24W	Ø125mm	220VAC	1,20 Kg	
Recessed COB Downlight	350418	4000K	2310 lm					
Recessed COB Downlight	350618	6500K	2450 lm					

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X=0 White Y=3 3000K
 2 Grey 4 4000K
 3 Black 6 6500K