




DT13


Track LED Lighting



HOUSING

Electrostatic powder paint coated die cast aluminum housing
IP20 Protection
Electrical Safety Class II


Body Color Options



OPTIC

Aluminium Reflector
UGR (CIE Pub.117):11
IEC/EN 62471 Photo-Biologic Protection RG0

Optic Options



LED

COB LED with a minimum lifetime of 100.000 hours
High color rendering (CRI>80)

Color Rendering Index



CCT



CONTROL

Rated Input Voltage 220~240VAC
Range of Input Voltage 176~264 VAC
Frequency 50~60Hz
Power Factor PF>0.60 (P≤25W) / PF>0.95 (P≥25W)
Operating Temperature -20°C ~ +50°C
Constant Current LED Driver









Additional Features



Over Current Protection (OCP), Over Voltage Protectio (OVP),
Short Circuit Protection (SCP), Over Temperature Protection (OTP)

STANDARDS

Luminaire Standarts EN 60598-1 - EN 60598-2-1
Driver Standarts LVD (EN 61347-1, EN 61347-2-13)
EMC (EN 55015, EN 61547, EN 61000-3-2/3-3)

 DT13-0060		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>10W</td> <td>1231 lm</td> <td>98 lm/W</td> </tr> <tr> <td>GU10</td> <td>- lm</td> <td>- lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	10W	1231 lm	98 lm/W	GU10	- lm	- lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-
Power	Lum. Flux	Efficiency																								
10W	1231 lm	98 lm/W																								
GU10	- lm	- lm/W																								
Packaging Sizes																										
Width	- cm																									
Length	- cm																									
Height	- cm																									
Amount per ctn.	- pcs.																									
Ctn. weight	- kg																									
Deci	-																									
 DT13-0080		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>20W</td> <td>2284 lm</td> <td>112 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	20W	2284 lm	112 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-			
Power	Lum. Flux	Efficiency																								
20W	2284 lm	112 lm/W																								
Packaging Sizes																										
Width	- cm																									
Length	- cm																									
Height	- cm																									
Amount per ctn.	- pcs.																									
Ctn. weight	- kg																									
Deci	-																									
 DT13-0100		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>30W</td> <td>3376 lm</td> <td>103 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	30W	3376 lm	103 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-			
Power	Lum. Flux	Efficiency																								
30W	3376 lm	103 lm/W																								
Packaging Sizes																										
Width	- cm																									
Length	- cm																									
Height	- cm																									
Amount per ctn.	- pcs.																									
Ctn. weight	- kg																									
Deci	-																									
 DT13-0118		<table border="1"> <thead> <tr> <th>Power</th> <th>Lum. Flux</th> <th>Efficiency</th> </tr> </thead> <tbody> <tr> <td>40W</td> <td>4102 lm</td> <td>109 lm/W</td> </tr> </tbody> </table>	Power	Lum. Flux	Efficiency	40W	4102 lm	109 lm/W	<table border="1"> <thead> <tr> <th colspan="2">Packaging Sizes</th> </tr> </thead> <tbody> <tr> <td>Width</td> <td>- cm</td> </tr> <tr> <td>Length</td> <td>- cm</td> </tr> <tr> <td>Height</td> <td>- cm</td> </tr> <tr> <td>Amount per ctn.</td> <td>- pcs.</td> </tr> <tr> <td>Ctn. weight</td> <td>- kg</td> </tr> <tr> <td>Deci</td> <td>-</td> </tr> </tbody> </table>	Packaging Sizes		Width	- cm	Length	- cm	Height	- cm	Amount per ctn.	- pcs.	Ctn. weight	- kg	Deci	-			
Power	Lum. Flux	Efficiency																								
40W	4102 lm	109 lm/W																								
Packaging Sizes																										
Width	- cm																									
Length	- cm																									
Height	- cm																									
Amount per ctn.	- pcs.																									
Ctn. weight	- kg																									
Deci	-																									

**The specified luminous flux values may vary by %10.

ORDER CODE EXPENSION

DT13- 0100 - 030 - 8 65 S - 9005-0045- 0 S S S 20

GROUP CODE	BODY CODE	POWER	CRI	CCT	EFFICIENCY	BODY COLOR	OPTIC	CONTROL	DRIVER	KIT	ACCESSORY	IP
DT13	0060 0080 0100 0118	010: 10W 020: 20W 030: 30W 040: 40W G10: GU10	8: 80	27: 2700K 30: 3000K 40: 4000K 65: 6500K	S: Standart	9016: White 9005: Black	0015: 15° 0030: 30°	0: ON-OFF	S: LAMPTIME	S: Standart	M: Monofaze T: Trifaze	20: IP20