



LED Ceiling Lighting

Housing
Polycarbonate Housing.

LED
SMD LED with high color rendering index
minimum lifetime of 100.000 hours (L70-85°C).


Sensor
High detection sensitivity
Adjustable time and lux feature.

Time Delay
10sn-3dk

Detection Distance
Maks. 8m

Mounting Height
2,2m±60cm



Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Voltage	Weight	Measurements
LED Ceiling Lighting	530301	3000K	1310 lm	16W	220VAC	0,75 Kg	
LED Ceiling Lighting	530401	4000K	1360 lm				
LED Ceiling Lighting	530601	6500K	1408lm				
LED Ceiling Lighting with sensor	531301	3000K	1310 lm	16W	220VAC	0,75 Kg	
LED Ceiling Lighting with sensor	531401	4000K	1360 lm				
LED Ceiling Lighting with sensor	531601	6500K	1408lm				
LED Ceiling Lighting with sensor Emergency Func.	532301	3000K	1310 lm	16W	220VAC	0,75 Kg	
LED Ceiling Lighting with sensor Emergency Func.	532401	4000K	1360 lm				
LED Ceiling Lighting with sensor Emergency Func.	532601	6500K	1408lm				

(1) The specified luminous flux values may vary bay %10.

(2) 530Y0X X=0 White Y=3 3000K
2 Grey 4 4000K
3 Black 6 6500K