



## High Bay Lighting IP65

### Housing

Electrostatic powder paint coated die cast aluminum housing.

### LED

≥ 100.000 hours L70 Performance 3030 Mid Power LED with high color rendering index.

### Driver

High efficiency constant current driver.

### Option

- ▶ Programmable DIM.
- ▶ 0-10V DIM.
- ▶ PWM.

### Light Angle



### Light Color



Product Name	Order Code <sup>(2)</sup>	CCT (K)	Luminous Flux <sup>(1)</sup>	Power	Voltage	Weight	Measurements
High Bay Lighting	801333	3000K	13365 lm	100W	220VAC	5,09 Kg	
High Bay Lighting	801433	4000K	14030 lm				
High Bay Lighting	801633	6500K	14740 lm				
High Bay Lighting	801334	3000K	21090 lm	150W	220VAC	5,09 Kg	
High Bay Lighting	801434	4000K	22140 lm				
High Bay Lighting	801634	6500K	23250 lm				
High Bay Lighting	801335	3000K	23650 lm	200W	220VAC	5,09 Kg	
High Bay Lighting	801435	4000K	24380 lm				
High Bay Lighting	801635	6500K	25600 lm				

(1) The specified luminous flux values may vary bay %10.

(2) 32XY42 X=0 White Y=3 3000K  
 2 Grey 4 4000K  
 3 Black 6 6500K