



Surface Mounted LED Lighting

Housing

Elektrostatik toz boyalı alüminyum.

Diffüzer

Opal diffüzer yüksek geçirgenlik.

LED

SMD LED yüksek renk verimliliği minimum ömür 100.000 saat (L70-85°C).

Driver

Doğru akım çıkışı, yüksek verimlilikli sürücü.

Option

- Acil aydınlatma kit 1 veya 3 saat süre için.
- DIM/DALI DIM

Housing Color



Light Angle



Light Color



Product Name	Order Code ⁽²⁾	CCT (K)	Luminous Flux ⁽¹⁾	Power	Voltage	Weight	Measurements
Surface Mounted LED Lighting 1000mm	290306	3000K	2150 lm	60W	220VAC	3,50 Kg	
Surface Mounted LED Lighting 1000mm	290406	4000K	2400 lm				
Surface Mounted LED Lighting 1000mm	290606	6500K	2640 lm				
Surface Mounted LED Lighting 1200mm	290307	3000K	2820 lm	75W	220VAC	4,20 Kg	
Surface Mounted LED Lighting 1200mm	290407	4000K	3000 lm				
Surface Mounted LED Lighting 1200mm	290607	6500K	3230 lm				
Surface Mounted LED Lighting 1500mm	290308	3000K	3410 lm	90W	220VAC	4,90 Kg	
Surface Mounted LED Lighting 1500mm	290408	4000K	3600 lm				
Surface Mounted LED Lighting 1500mm	290608	6500K	3770 lm				

(1) The specified luminous flux values may vary by %10.

(2) 32XY42 X=0 White Y=3 3000K
 2 Grey 4 4000K
 3 Black 6 6500K